



Protective UV Tapes

3W25X • 3W26X • 3W29X (Black/White)

Technical Data

March, 2007

Product Description 3M™ Protective UV Tapes are a line of black and white co-extruded polyethylene tapes for temporary indoor and outdoor protection of many metals, plastics and glass.*

Construction	Backing	Adhesive	Colors	Standard Roll Size
	Polyethylene	Acrylic	White (outside layer) Black (inside adhesive layer)	48 in. (1200 mm), 60 in. (1500 mm), 72 in. (1800 mm) x 1000 ft. (304.8 m) to 5000 ft. (1524 m)

Typical Physical Properties and Performance Characteristics

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

	Nominal Results			ASTM Test Method
	3M™ Protective UV Tapes			
Adhesion to Steel: (oz./in. width)	3W25X 5	3W26X 7	3W29X 8	D-3330
Tack Level:	Medium	Medium	Medium	
Tensile Strength: (Break or Yield)	2500 PSI / 1.7 MPA			D-882
Elongation: (Break or Yield)	450%			D-882
Total Tape Thickness:	3.0 mils (0.08 mm)			D-3652

Features

- Black/white tape does not lift and removes cleanly after exposure to sunlight.
- Helps protect surfaces and reduces replacement of parts because of surface abrasion.
- Abrasion-resistant backing resists tearing during forming.
- Stable adhesion levels result in good removability during application life.
- Excellent UV resistance for up to 6 months.*

*UV performance was generated from actual exposure in South Eastern USA on selected painted metal surfaces. Accelerated laboratory weathering tests were performed on representative painted metal surfaces. **Pre-qualification testing at 3M PolyMask may not predict actual results obtained under customer process and environmental conditions and use on specific substrates so customer qualification testing and evaluation are required prior to use.** Contact technical service at 3M PolyMask for assistance @ 1-800-241-2031.

Application Ideas

- Protects stainless steel 304 2B, brushed aluminum, embossed and smooth painted metals, fiberglass and molded plastics, cultured marble, solid surface counter tops and glass that will be exposed to outdoor environments.

Application Techniques

For optimum performance, these tapes should be applied and removed at a temperature not less than 60°F (16°C).

3M™ Protective UV Tapes

3W25X • 3W26X • 3W29X (Black/White)

Storage Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton.

Shelf Life To obtain best performance, use this product within 12 months from date of manufacture.

For Additional Information To request additional product information or to arrange for sales assistance, call toll free 1-800-241-2031 or 828-465-3053. Address correspondence to: PolyMask, a 3M company, 500 Thornburg Dr., P.O. Box 309, Conover, NC 28613. Our fax number is 1-800-672-3038 or 828-465-2404.

Product Use All statements, technical information and recommendations contained in this document are based upon tests or experience that PolyMask Corporation and 3M believe are reliable. However, many factors beyond the control of PolyMask Corporation and 3M can affect the use and performance of a PolyMask Corporation and 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the PolyMask Corporation and 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy Unless stated otherwise in other product literature, packaging inserts or product packaging for individual products, PolyMask Corporation and 3M warrants that each PolyMask Corporation and 3M product meets the applicable specifications at the time PolyMask Corporation and 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. **POLYMASK CORPORATION AND 3M COMPANY MAKE NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.** User is responsible for determining whether the PolyMask Corporation and 3M product is fit for a particular purpose and suitable for user's application. If the PolyMask Corporation and 3M product is defective within the warranty period, your exclusive remedy and PolyMask Corporation and 3M's sole obligation will be, at PolyMask Corporation and 3M's option, to replace the product or refund the purchase price.

Limitation of Liability Except where prohibited by law, 3M Company and PolyMask Corporation, will not be liable for any loss or damage arising from the PolyMask Corporation and 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2000

This product was manufactured under a quality system registered to ISO 9001:2000 standards by PolyMask Corporation, a 3M company.



**Industrial Business
Industrial Adhesives and Tapes Division**

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000
www.3M.com/protectivetapes



*Recycled Paper
40% pre-consumer
10% post-consumer*

PolyMask Corporation is a 3M Company.
3M is a trademark of 3M Company.
Printed in U.S.A.
©3M 2007 70-0709-4955-0 (3/07)