

3M™ Overhead Projector

Model 1810 Plus



Dependable and Durable

The 3M™ Overhead Projector 1810 *Plus* is engineered for durability with a chemically-hardened, break-resistant stage glass. The durable stage glass can result in less maintenance, interruptions and repair expenses. The 1810 *Plus* offers an open-singlet wide-angle lens and 2,700 lumens of light output for vivid images, even in lighted rooms. This value-priced projector combines the smoothness of elegant boardroom styling with rugged classroom functionality at an affordable price, without sacrificing image quality. A global leader in overhead projectors, 3M provides a five-year limited warranty on parts and labor.

KEY FEATURES

- > Chemically-hardened stage glass is retained by clips for easy replacement.
- > Open-singlet projection head for easy cleaning.
- > Wide-angle lens produces large images in the smallest rooms.
- > Dual element fresnel lens for a sharper screen image.
- > 2,700-lumen light can enhance your visuals even with room lights on for note taking.
- > Convenient fold-down post makes for easy storage.
- > Built-in resistor to extend lamp life.
- > 10.5" X 10.5" staging area gives you room to maximize your message.
- > Built-in pen tray for convenient storage.
- > Fifteen-foot power cord and tangle-free cord storage.
- > Five-year limited warranty on parts and labor. Please see product packaging for details of warranty terms.
- > One lamp included.

ORDER NUMBER: 78-9236-6856-6

OPTIONAL ACCESSORIES: Replacement lamp, roller attachment, roller-attachment film, dust cover, and projection screens.

TECHNICAL SPECIFICATIONS

OPTICAL PERFORMANCE

- > Head: **Open-singlet** (*one element lens*), **wide-angle**
- > Illumination: **2,700 ANSI lumens typical***
- > Design: **Transmissive with folded optical system**
- > Focal length: **11.5"** (293 mm)
- > Stage aperture: **10.5" x 10.5"** (267 mm x 267 mm)
- > Fresnel Lens: **Dual Element Lens**

LAMP DESCRIPTION

- > **Lamp ejector**
- > **1 Lamp included**
- > Lamp type: **ENX** (82 volts, 360 watts)
- > Lamp life: **75 hours** ANSI rating
- > Built-in resistor to **extend lamp life** well beyond the 75 hour ANSI rating*

ELECTRICAL FEATURES

- > Power-cord length: **15'** (4.6 m)
- > **Power-cord wrap**

MECHANICAL

- > **Thermal protection circuit:** cuts power to the lamp if the projector exceeds safe operating temperature
- > Weight: **18.8 lbs.** (8.5 kg)



*Using 3M ENX Lamps

1.800.328.1371

www.3M.com/meetings

Specifications subject to change without notice.

3M is a trademark of 3M Company. Used under license in Canada. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

3M Visual Systems
Building A147-5N-01
6801 River Place Blvd.
Austin, TX 78726-9000
1-800-328-1371
www.3m.com/meetings

3M Visual Systems
3M Canada Company
P.O. Box 5757
London, Ontario, Canada
N6A 4T1
1-800-364-3577

3M Mexico, S.A. de C.V.
Apartado Postal 14-139
Mexico, D.F. 07070
Mexico

© 3M 2005
R122905
78-6970-8493-4

Important Notice.

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of five years from the date of purchase. 3M MAKES NO OTHER WARRANTIES or CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

3M Innovation