

3M™ Overhead Projector

Model 1895M

Fully Featured

The 3M™ Overhead Projector 1895M is engineered for durability with a chemically hardened, break-resistant stage glass. The durable stage glass can result in less maintenance, interruptions and repair expenses. The 1895M packs a high-resolution, three-element lens for incredible brightness, maximum resolution, and very sharp images. The lamp changer makes replacing lamps a simple job. The fully loaded 3M Overhead Projector 1895M is backed by a five-year limited warranty on parts and labor.



KEY FEATURES

- > Chemically hardened stage glass is retained by clips for easy replacement.
- > Utmost in brightness— typical minimum output of 3,600 lumens to a maximum of 4,000 lumens
- > Dual element fresnel lens for a sharper screen image
- > Built-in resistor to extend lamp life.
- > Lamp interrupt switch shuts off power to a lamp when changing lamps to prevent premature lamp failure
- > High/low lamp switch for high brightness or extended lamp life.
- > Convenient carrying handle and fold-down post provide optimal portability and storability.
- > 10.5" x 10.5" staging area gives you room to maximize your message.
- > Built-in pen tray for convenient storage
- > Fifteen-foot power cord and tangle-free cord storage
- > Five-year limited warranty on parts and labor. Please see product packaging for details of warranty terms.
- > Two lamps included.

ORDER NUMBER: 78-9236-6881-4

OPTIONAL ACCESSORIES: Replacement lamp, roller attachment, roller-attachment film, dust cover, and projection screens.

TECHNICAL SPECIFICATIONS

OPTICAL PERFORMANCE

- > Head: **Open triplet** (three-element) lens
- > Illumination: **4,000 ANSI lumens expected typical** (3,600 lumens – typical for low setting)*
- > Design: **Transmissive** with folded optical system
- > Focal Length: 13.5" (342 mm)
- > Stage aperture: **10.5" x 10.5"** (267mm x 267mm)

LAMP DESCRIPTION

- > **Lamp ejector**
- > **2 Lamps included**
- > **Lamp changer**
- > Lamp Type: **FXL** (82 volts, 410 watts)
- > Lamp Life: **38** hours ANSI rating
- > Built-in resistor **to extend lamp life** well beyond the 38 hour ANSI rating.
- > High/low switch **to enhance brightness** or **extend lamp life**.

PHYSICAL CHARACTERISTICS

- > Weight: **19.5 lbs.** (8.9 kg)

ELECTRICAL FEATURES

- > **High/low switch**
- > Power-cord length: **15 feet** (4.6 m)
- > **Power-cord wrap**

MECHANICAL

- > **Lamp-interrupt switch** shuts off power to the lamp when changing to prevent premature failure
- > **Carrying handle**
- > **Fold-down post**



*Using 3M FXL Lamps

1.800.328.1371

www.3M.com/meetings

Specifications subject to change without notice.

3M is a trademark of 3M Company. Used under license in Canada. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

3M Visual Systems

Building A147-5N-01
6801 River Place Blvd.
Austin, TX 78726-9000
1-800-328-1371
www.3m.com/meetings

3M Mexico, S.A. de C.V.

Apartado Postal 14-139
Mexico, D.F. 07070
Mexico

3M Visual Systems

3M Canada Company
P.O. Box 5757
London, Ontario, Canada
N6A 4T1
1-800-364-3577

© 3M 2007
v02.13.07

78-6970-8494-1

Important Notice.

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of five years from the date of purchase. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

3M